

CERTIFICATE OF CONSTANCY OF PERFORMANCE

1239/CPR/0821004

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products, it's certified that the

Construction product: **Timber structures. Glued laminated timber.**

Scope of Certification: **see Annex**

Provided by: **EGOIN, S.A.
Cº Astei
48287 - NATXITUA-EA (Bizkaia) SPAIN**

Produced in: **Polígono Gojain
c/ Padurea nº2 B
01170 – LEGUTIANO (Araba) SPAIN**

Is subject to a factory production control and to the inspection of samples in accordance to a prescribed test plan by the manufacturer, and that the Notified Body TECNALIA R&I CERTIFICACION S.L. has carried out initial type tests for all relevant characteristics of the product, as well as the initial inspection of the factory and FPC, and the continuous surveillance, assessment and approval of FPC

This certificate shows compliance with all regulations applicable to the conformity assessment in the Annex ZA of the standard

EN 14080:2013

and that the product meets the minimum requirements applicable.

System of assessment and verification of constancy of performance : SYSTEM 1

Issued on: 11/10/2016
Last modified on: 21/02/2023
Expires on: 24/09/2025
Nº serie: 082100402-E

tecnal:a
certification

Firmado digitalmente por
15966973M CARLOS
MANUEL NAZABAL (R:
B20991220)

Carlos Nazabal Alsua
Manager



This document allows the manufacturer to fix the CE mark.
This certificate may be modified, temporarily suspended and withdrawn by TECNALIA R&I CERTIFICACION.
The validity of this certificate can be checked through consultation in www.tecnaliacertificacion.com

ANNEX
CERTIFICATE OF CONSTANCY OF PERFORMANCE
1239/CPR/0821004

Construction product: Glued laminated timber.

Strength class:	GL24h
• Wood specie:	Alerce (<i>Larix decidua</i>) Pino Radiata (<i>Pinus radiata</i>)
Service classes:	1, 2 and 3
Adhesive:	MUF TYPE I according to EN 301:2013
Fire performance:	D-s2,d0
Formaldehyde class:	E1
Natural durability class:	Alerce (<i>Larix decidua</i>): 3-4/D-D/S/S Pino Radiata (<i>Pinus radiata</i>): 4-5/D-S/S/S
Preventive treatment:	EN 15228 Wood specie: Pino Radiata Usage type: 4