

CERTIFICATE OF CONSTANCY OF PERFORMANCE

1239/CPR/0821001

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products, it's certified that the

Construction product: **Structural finger jointed solid timber**
Scope of Certification: **see Annex**
Provided and Produced by: **EGOIN, S.A.
Cº Astei
48287 - NATXITUA-EA (Bizkaia) SPAIN**

Is subject to a factory production control and to the inspection of samples in accordance to a prescribed test plan by the manufacturer, and that the Notified Body TECNALIA R&I CERTIFICACION S.L. has carried out initial type tests for all relevant characteristics of the product, as well as the initial inspection of the factory and FPC, and the continuous surveillance, assessment and approval of FPC

This certificate shows compliance with all regulations applicable to the conformity assessment in the Annex ZA of the standard

EN 15497:2014

and that the product meets the minimum requirements applicable.

System of assessment and verification of constancy of performance : SYSTEM 1

Issued on: 04/07/2016
Last modified on: 21/02/2023
Expires on: 24/09/2025
Nº serie: 082100104-E

tecnal:a
certification

Firmado digitalmente por
15966973M CARLOS MANUEL
NAZABAL (R: B20991220)

Carlos Nazabal Alsua
Manager



This document allows the manufacturer to fix the CE mark.
This certificate may be modified, temporarily suspended and withdrawn by TECNALIA R&I CERTIFICACION.
The validity of this certificate can be checked through consultation in www.tecnaliacertificacion.com

ANNEX
CERTIFICATE OF CONSTANCY OF PERFORMANCE
1239/CPR/0821001

Construction product: Structural finger jointed solid timber.

Wood species:	Radiata pine (<i>Pinus Radiata</i>, <i>PNRD</i>)
Strength class:	C24
Maximum dimension:	60 x 140 mm
Service classes: (according to EN 1995-1-1)	1, 2 and 3
Adhesive:	PUR Type I according to EN 15425:2009
Fire performance:	D-s2, d0
Formaldehyde class:	E1
Natural durability class:	4-5/D-S/S/S
Preventive treatment:	EN 15228:2009 Usage type: 4